



www.first-last-always.com

MAINTENANCE OF OSMO HARDWAX OILED FLOORS:

- Keep grit off the floor.
- Dust mop or vacuum regularly and keep doormats clean.
- Wipe up spills promptly with a dry cloth.
- Use a slightly dampened cloth for sticky spills.
- For general weekly or periodic cleaning, mix 1 cover cup of Osmo Wash And Care with a quart of warm water. Shake the product well prior to mixing. Clean the floor with the diluted soap and a floor cloth, a sponge mop or a wet mop. Always make sure that you wring out the applicator well in order to avoid excessively wetting the floor. Avoid penetration of water into joints of floor boards. You can also use a spray bottle and spray small amount of a diluted cleaner on mop or cloth, and wipe small section of floor. Buff dry. Continue until entire area has been cleaned.

HARDWAX OILED FLOORS REQUIRE PROFESSIONAL ANNUAL MAINTENANCE OF AT LEAST MAIN TRAFFIC AREAS. PLEASE CALL US TO INSPECT YOUR FLOORS ANUALLY AND TO ASSIST YOU WITH NECESSARY RECOATS.

PREVENTION:

1. Use only proper floor care products.
2. Place mats at doorway exteriors to minimize trucking of grit, dirt and sand.
3. Wipe all spills immediately.
4. Put fabric or plastic- faced glides under the legs of furniture, to prevent scuffing and scratching.
5. Cleats, high heels can dent any floor surface!
6. Do not slide heavy pieces of furniture on the floor.
7. For wood flooring in the kitchen, place an area rug in front of the kitchen sink.